

Product				European Style & Cassette Type Fan Coil Unit											
Type				2pipes											
Model-RFPC				34-2	51-2	68-2	80-2	85-2	102-2	136-2	170-2	204-2	238-2	289-2	340-2
				200	300	400	450	500	600	800	1000	1200	1400	1700	2000
Air Flow (m ³ /h)	H	(m ³ /h)		340	510	680	765	850	1020	1360	1700	2040	2380	2890	3400
	M			280	390	520	580	640	790	1030	1700	2040	2380	2890	2600
	L			180	260	350	390	430	520	690	860	1030	1200	1600	1900
Cooling	Total capacity	H	KW	2	2.7	3.7	4.2	4.5	5.6	7	9.1	10.8	12.6	15.3	17.6
		M	KW	1.8	2.3	3.1	3.8	4.2	4.3	5.7	7.9	8.6	10	11.7	13.5
		L	KW	1.6	1.8	2.6	2.8	3	3.6	4.5	6	6.8	8	9.3	9.9
	Sensible capacity	H	KW	1.5	1.9	2.6	2.9	3.5	3.9	5	6.4	7.7	9	11.5	14.8
		M	KW	1.3	1.7	2	2.6	3.2	3.3	4.3	5.9	6.5	7.5	8.4	11.1
		L	KW	1.2	1.4	1.8	1.9	2.8	2.9	3.6	4.8	5.4	6.4	6.8	7.8
	Water Flow			l/h	345	470	640	720	780	970	1260	1710	1920	2160	2640
Water P.D			kPa	7	9	11	14	16	18	19	17	19	22	36	48
Heating	Heating capacity	H	KW	2.8	4.2	5.6	6.3	7	8.4	11.2	13.9	16.7	19.5	23.7	25.5
		M		2.5	3.4	4.5	5.5	6.3	6.5	8.5	12	12.6	15.6	17.5	18.6
		L		2	2.7	4	4.5	5	5.2	6.7	9	10.2	12	13.8	13
Power supply				220-240V/1PH/50HZ(60HZ)											
Power Input			W	37	39	41	42	43	45	46	47	50	52	57	65
Sound pressure			dB(A)	37	39	41	42	43	45	46	47	50	52	57	65
Fan	Type			Centrifugal Fan											
	Model			Φ315											
	Qty			1	1	1	1	1	1	1	1	1	1	1	1
Motor	Type			3-speed											
	Qty			1	1	1	1	1	1	1	1	1	1	1	1
Coil	Rows			2											
	Mix.working		MPa	1.6Mpa											

	Tube Dia	inch	3/8"											
Dimension	Unit body	mm	580x580x250	705x705x290	832x832x290	960x960x290								
	Panel assembly	mm	680x680x30	830x830x30	980x980x30	1140x1140x30								
Connection	Water inlet/outlet	inch	ZG3/4" / ZG3/4"											
	Condensate discharge	inch	26											
	Weight	Kg	20	20	20	20	25	25	25	34	34	34	50	52

Product				European Style & Cassette Type Fan Coil Unit										
Type				4pipes										
Model-RFPC				68-2+1	80-2+1	85-2+1	102-2+1	136-2+1	170-2+1	204-2+1	238-2+1	289-2+1	340-2+1	
				400	450	500	600	800	1000	1200	1400	1700	2000	
Air Flow (m ³ /h)		H	(m ³ /h)	680	765	850	1020	1360	1700	2040	2380	2890	3400	
		M		520	580	640	790	1030	1290	1500	1800	2100	2600	
		L		350	390	430	520	690	860	1030	1200	1600	1900	
Cooling capacity(W)		Total capacity	H	KW	2.6	2.8	3.1	3.6	4.8	6	7	8.4	10.3	11.5
			M	KW	2	2.2	2.4	2.8	3.7	4.7	6	6.5	7.5	8.3
			L	KW	1.4	1.6	1.8	2.1	3	3.6	4.6	5	5.7	6.3
		Sensible capacity	H	KW	1.8	2	2.2	2.5	3.4	4.2	4.9	5.9	8.5	9.5
			M	KW	1.5	1.6	1.8	2.1	2.8	3.5	4.5	4.9	6.2	6.9
			L	KW	1.1	1.2	1.4	1.7	2.4	2.9	3.7	4	4.7	5.2
		Water Flow		I/h	450	468	540	625	830	1050	1400	1500	1800	2000
Water P.D		kPa	11	13	17	17	19	21	23	25	27	29		
Heating capacity(W)		Heating capacity	H	KW	2.6	3.1	3.5	4.3	4.9	6.5	7.2	8.7	11.9	15.2
			M		2	2.3	2.7	3.2	4.3	5.4	5.6	7.6	8.7	11.3
			L		1.4	1.7	2.1	2.5	3.5	4.2	4.3	5.8	6.6	8.7
Power supply				220-240V/1PH/50HZ(60HZ)										
Power Input			W	62	68	76	96	132	152	189	220	330	340	
Sound pressure			dB(A)	41	42	43	45	46	47	50	52	57	65	
Fan		Type		Centrifugal Fan										
		Model		Φ315										
		Qty		1	1	1	1	1	1	1	1	1	1	
Motor		Type		3-speed										
		Qty		1	1	1	1	1	1	1	1	1	1	
Coil		Rows		2										
		Mix.working		MPa	1.6Mpa									

	Tube Dia	inch	3/8"									
Dimension	Unit body	mm	580x580x250	705x705x290			832x832x290			960x960x290		
	Panel assembly	mm	680x680x30	830x830x30			980x980x30			1140x1140x30		
Connection	Water inlet/outlet	inch	ZG3/4" / ZG3/4"									
	Condensate discharge	inch	26									
	Weight	Kg	21	21	26	26	26	35	35	35	53	53